

1.0m Quick-Deploy Antenna System

Ku-Band Option

Features

- 2 or 6-Piece Aluminum Reflector
- Pre-Assembled Tripod or Low Profile Mount w/Pull Pins
- C, Ku and Ka Band Feed Systems Available
- Sturdy Boom Accommodates Outdoor Units
- Adjustable Feet for Uneven Surfaces
- Optional Lightweight Cases for Easy Transportation
- Azimuth and Elevation Hand Crank
- 10 Minute Setup, No Tools Needed

Description

The Challenger Communications 1.0 Meter Quick-Deploy Antenna System incorporates precision assembled reflector panels with our rugged **Antenna Armor™** backing structure.

To ensure quality and performance, Challenger panels are inspected for R.M.S. accuracy using the latest in laser measurement techniques.

All reflectors and mounts are produced from high quality materials and are made in the USA.

RF & Antenna Specifications	Ku Linear	
	Receive	Transmit
Frequency (GHz)	10.7 - 12.75	13.75 - 14.5
Antenna Gain*	39.3 @ 11.7 GHz	41.4 @ 14.25 GHz
Antenna Noise Temperature @ 10.7 GHz		
10° Elevation	66K	
20° Elevation	54K	
30° Elevation	52K	
Cross Polarization Isolation		
On Axis	>30 dB	>30 dB
within 1 dB Beamwidth	>25 dB	>26 dB
VSWR	<1.5:1	<1.2:1
Port to Port Isolation	>45 dB	>80 dB
Feed Interface	WR75	WR75
Sidelobe Performance		ITU-R S.580

Mechanical Specifications	
Antenna Optics	Offset, Prime Focus
Mount Type	Azimuth over Elevation
Elevation Adjustment	0° to 90°
Azimuth Adjustment	360° Continuous Fine Adjustment

Durable Nylon backpack-style case with rollers and extension handle:

65 lbs. 34 x 20 x 15 in. (29.5 kg 86.4 x 50.8 x 15 cm)

Hard cases option also available.

Environmental Performance	Standard	Metric
Wind Loading	Standard	Metric
Operational (No Ballast/Anchors)	20 mph	32.2 km/h
Survival (w/Ballast/Anchors)	30-45 mph gusts	48.3-72 km/h gusts
Operational Temperature	15° to 125°F	9.4° to 51.7°C
Survival Temperature	-45° to 140°F	-42.8° to 60°C
Rain	.5 in./h	1.3 cm/h
Solar Radiation	360 BTU/h/ft²	1000 Kcal/h/m²



1.0m Quick-Deploy Antenna System
6-piece reflector with low profile mount depicted

*Includes all losses

Made in the USA

Challenger Communications
704 North Clark Street
Albion, Michigan 49224 USA
Tel: +1 (517) 680 0125
Fax: +1 (517) 680 0133
info@challengercommunications.com
www.ChallengerCommunications.com